

PHOTOLUMINESCENT EXIT SIGNS

Non Radioactive ♦ Non Electrical ♦ Standard or Directional

LOW LEVEL ALUMINUM EXIT MARKERS

MODEL # CE13.100XS

Specifications

**Contains no
Tritium !**



Marker Size:	7" height 13" width 3/8" depth single-face 1 1/8" depth double-face
Letter size:	3/4" stroke with 6" height
Letter color:	Green or Red
Background:	Green illuminating
Mounting:	Surface snap mount: snap-on clips attach to wall, sign snaps onto clips. Ceiling, T-bar attachment with hanging cables.
Activation:	3-5 foot-candles ambient lighting
Directional:	Optional field applied vinyl arrows
Life expectancy:	Twenty-five years+
Construction:	Aluminum extrusion with self-illuminating coating
Maintenance:	None
Attributes:	Non-electrical, non-radioactive, explosion proof, ASTM E 162 Flame spread Index., 22.88
Listing Reports:	Underwriters Laboratories Listed Pursuant to Standard UL1994. Low Level Pathway & Low Level Exit Markings California State fire Marshal Listing #6210-1371:1 01 San Francisco Research Report and Product Approval # 10440ACT, Los Angeles Research Report and Product Approval #RR-25083-T, US Test Report #182556-1 ICBO listing # 5101

Model Number	Description	NSN Red Letters	NSN Green Letters
CE13.100XS-SW	Single Face Wall Mount Snap Mount Aluminum	6240-01-490-0979	6240-01-490-5050
CE13.100XS-SC	Single Face, Ceiling (T bar Attachment only) Aluminum	6240-01-490-0980	6240-01-490-5052
CE13.100XS-D	Double Face, Ceiling (T bar Attachment only) Aluminum	6240-01-490-1782	6240-01-490-5054
Field Applied Arrows NSN 6220-01-490-1833			



CORPORATE ENERGY MANAGEMENT SYSTEMS, INC.

PHOTOLUMINESCENT EXIT SIGNS

Non Radioactive ♦ Non Electrical ♦ Standard or Directional

LOW LEVEL ALUMINUM EXIT MARKERS

MODEL # CE14.100XS

Specifications

Marker Size:	7" height 13" width 1/8" depth single-face
Letter size:	1" stroke with 6" height
Letter color:	Green illuminating
Background:	Black, Brushed Aluminum, White or Custom Finish
Mounting:	Flush wall mount
Activation:	3-5 foot-candles ambient lighting
Directional:	Pop out arrows
Life expectancy:	Twenty-five years+
Construction:	Stenciled aluminum face plate, beveled edges & photo-luminescent text
Maintenance:	None
Attributes:	Non-electrical, non-radioactive, explosion proof, ASTM E 162 Flame spread Index., 22.88
Listing Reports:	Underwriters Laboratories Listed Pursuant to Standard UL1994. Low Level Pathway & Low Level Exit Markings California State fire Marshal Listing #6210-1371:1 01 San Francisco Research Report and Product Approval # 10440ACT, Los Angeles Research Report and Product Approval #RR-25083-T, US Test Report #182556-1 ICBO listing # 5101



***Contains no
Tritium !***

Model Number	Description	NSN
CE14.100XS-SW W	Single Face Wall Mount Aluminum, White	6240-01-490-1786
CE14.100XS-SW B	Single Face, Wall Mount Aluminum, Black	6240-01-490-1818
CE14.100XS-SW BA	Single Face, Wall Mount Aluminum, Brushed Aluminum	6240-01-490-1788



CORPORATE ENERGY MANAGEMENT SYSTEMS, INC.